







MATCHED MECHANISM ID NEED
TO AVOID INTERFERENCE WITH
TERMINAL WHEN PLUG IN



DATE CODE:

YY MM DD
DAY
MONTH
YEAR



PCB HOLES(TOP VIEW) t=1.0mm
NOTE:GENERAL TOLERANCE:±0.05mm

NOTES:

- MATERIAL: SEE "TABLE 1";
- FINISH: SEE "TABLE 1";
- ELECTRICAL:
 - VOLTAGE RATING: 12 VAC RMS;
 - CURRENT RATING: 0.5 AMP;
 - CONTACT RESISTANCE: 50mΩ Max.(Initial), 100mΩ Max.(After Life test);
 - INSULATION RESISTANCE: 1000 MΩ Min., 500VDC.(Initial), 100 MΩ Min., 500VDC.(After Humidity test);
 - WITHSTAND VOLTAGE: 500 VAC RMS 50(60)Hz, 1 minute;
- MECHANICAL:
 - MATING FORCE: 3.0Kgf MAX.;
 - UNMATING FORCE: 0.3Kgf MIN.;
 - OPERATING LIFE: 5000 CYCLES MIN.;
- ENVIRONMENTAL:
 - OPERATION: -30°C~+80°C.

TABLE 1:










⑧	Contact_6	⑥	1	C5210-EH	CONTACT AREA: 1U*MIN SOLDER AREA:1U*MIN 50u" OVER ALL	T=0.20mm
⑦	Contact_5	⑤	1	C5210-EH		T=0.20mm
⑥	Contact_4	④	1	C5210-H		T=0.20mm
⑤	Contact_3	③	1	C5210-H		T=0.20mm
④	Contact_2	②	1	C5210-H		T=0.20mm
③	Contact_1	①	1	C5210-H		T=0.20mm
②	Separator		1	PA10T	BLACK,UL94V-0	
①	Housing		1	PA10T	BLACK,UL94V-0	
NO.	PART NAME	QTY	MATERIAL	DESCRIPTION	REMARK	



LZG INDUSTRIAL CO. LTD

PART NAME	ø3.50mm AUDIO JACK	TOLERANCE UNLESS	0.0±0.25	0.°±2°	UNIT: mm	
PART NO.	ZB23027-06FBAP-A	OTHERWISE SPECIFIED:	0.00±0.15 0.000±0.05	0.0°±1° 0.00°±0.5°		

DRAWING:	林生财	DATE:	2023.11.24	SCALE	1:1
CHECK:	李宏鑫	DATE:	2023.11.24	MATERIAL	*
APPROVAL:	杨进宝	DATE:	2023.11.24	DWG. NO.	
DRAWING NO.	ZB23027-06FBAP-A			SHEET	1/2



CARTON SIZE

1 CARTON = 10 REEL = 7500 PRODUCT

NOTES:

1. Material requirements:

1.1 The carton material requirements for the K=A,
Dimension is 350*340*310mm;

1.2 Reel materials for PET; size reel for 330*28.

2. Packaging requirements:

- 2.1 The tape into the packing machine, before the empty 16PCS, after the release of the product 750PCS,
- then the empty 16PCS with 256mm length of stay;
- 2.2 Top cover should out 100mm of the carrier tape. After winding, using adhesive tape(80-150mm) to stick the leader of cover tap on the side of the carrier tape;
- 2.3 Winding a protect tape around the reel, then stick it by adhesive tape;
- 2.4 label should paste in the designated area of the reel;
- 2.5 Put a dryer and a packed reel in the vacuum bag and make the vacuum process;
- 2.6 The tired folded 10 disks in the carton total 7500pcs;
- 2.7 Packed finished packing sealing, and in the outer carton label



LZG INDUSTRIAL CO. LTD

PART NAME	ø3.50mm AUDIO JACK	TOLERANCE UNLESS	0.0±0.25	0.°±2°	UNIT: mm	
PART NO.	ZB23027-06FBAP-A	OTHERWISE SPECIFIED:	0.00±0.15 0.000±0.05	0.0°±1° 0.000°±0.5°		

DRAWING:	林生财	DATE:	2023.11.24	SCALE	1:1
CHECK:	李宏鑫	DATE:	2023.11.24	MATERIAL	*
APPROVAL:	杨进宝	DATE:	2023.11.24	DWG. NO.	
DRAWING NO.	ZB23027-06FBAP-A			SHEET	2/2